



LP1360

TURNBUCKLES

Material

Steel (1.0037), zinc-plated.
Hot dip galvanized version, available on request providing increased protection

against corrosion. Please add -FZ for hot dip galvanized, e.g. LP1360.R006-FZ.

Important Notes

Turnbuckles are not to be used for lifting. Only suitable for use in tension.

Order No.	Thread hand	d ₁	d ₂	l ₁	l ₂	Weight kg
LP1360.R006	Right	M 6	10	74	50	0.015
LP1360.R008	Right	M 8	11	80	52	0.030
LP1360.R010	Right	M10	15	95	59	0.050
LP1360.R012	Right	M12	17	107	66	0.085
LP1360.R014	Right	M14	18	158	85	0.130
LP1360.R016	Right	M16	22	146	85	0.210
LP1360.R020	Right	M20	24	170	100	0.380
LP1360.R022	Right	M22	30	203	123	0.580
LP1360.R024	Right	M24	33	213	134	0.830
LP1360.R030	Right	M30	39	255	150	1.400
LP1360.R036	Right	M36	37	260	150	2.180
LP1360.R042	Right	M42	48	285	165	3.190
LP1360.R048	Right	M48	58	335	185	4.970
LP1360.L006	Left	M 6	10	74	50	0.015
LP1360.L008	Left	M 8	11	80	52	0.030
LP1360.L010	Left	M10	15	95	59	0.050
LP1360.L012	Left	M12	17	107	66	0.085
LP1360.L014	Left	M14	18	158	85	0.130
LP1360.L016	Left	M16	22	146	85	0.210
LP1360.L020	Left	M20	24	170	100	0.380
LP1360.L022	Left	M22	30	203	123	0.580
LP1360.L024	Left	M24	33	213	134	0.830
LP1360.L030	Left	M30	39	255	150	1.400
LP1360.L036	Left	M36	37	260	150	2.180
LP1360.L042	Left	M42	48	285	165	3.190
LP1360.L048	Left	M48	58	335	185	4.970