




Hooks for Turnbuckles

steel

Turnbuckles



LP1362

TURNBUCKLES

Material

Steel (1.0037).

Hot dip galvanized version, available on request providing increased protection

against corrosion. Please add -FZ for hot dip galvanized, e.g. LP1362.R006-FZ.

Important Notes

Turnbuckles are not to be used for lifting. Only suitable for use in tension.

Order No.	Thread hand	d ₁	l ₁	l ₂	w ₁	S.W.L. kg	Weight kg
LP1362.R006	Right	M 6	77.0	50	9.5	75	0.016
LP1362.R008	Right	M 8	98.0	60	11.0	165	0.034
LP1362.R010	Right	M10	116.5	73	14.0	235	0.060
LP1362.R012	Right	M12	146.0	90	18.0	320	0.113
LP1362.R014	Right	M14	140.0	80	16.0	420	0.170
LP1362.R016	Right	M16	165.0	100	19.0	530	0.275
LP1362.R020	Right	M20	180.0	105	21.0	730	0.440
LP1362.R022	Right	M22	215.0	120	26.0	1120	0.685
LP1362.R024	Right	M24	225.0	135	29.0	1550	0.765
LP1362.R030	Right	M30	225.0	140	31.0	2240	1.325
LP1362.R036	Right	M36	300.0	170	35.0	3530	2.285
LP1362.L006	Left	M 6	77.0	50	9.5	75	0.016
LP1362.L008	Left	M 8	98.0	60	11.0	165	0.034
LP1362.L010	Left	M10	116.5	73	14.0	235	0.060
LP1362.L012	Left	M12	146.0	90	18.0	320	0.113
LP1362.L014	Left	M14	140.0	80	16.0	420	0.170
LP1362.L016	Left	M16	165.0	100	19.0	530	0.275
LP1362.L020	Left	M20	180.0	105	21.0	730	0.440
LP1362.L022	Left	M22	215.0	120	26.0	1120	0.685
LP1362.L024	Left	M24	225.0	135	29.0	1550	0.765
LP1362.L030	Left	M30	225.0	140	31.0	2240	1.325
LP1362.L036	Left	M36	300.0	170	35.0	3530	2.285