




Captive Screws - Hex Bolts

316 stainless

Whilst Stocks
Last ...



application examples :-
counterbore length 'x₁' should be > l₂



T0158.A4

WHILST STOCKS LAST ...

Material

Stainless steel (AISI 316, 1.440).
Tensile strength 480 N/mm². Proof stress
min. 200 N/mm², austenitic stainless steel.
Also available on request in steel
(anodised, black oxide or zinc plated),
stainless steel (AISI 303, 1.4305), brass,
aluminium etc.

Technical Notes

Used to comply with the Machinery Direc-
tive 2006/42/EC. Often used with our
captive washers (CS1210) or retaining
flanges (- for sheet metal applications).
The use of our captive washers should be
considered when fitted in panels with
unthreaded holes.

Important Notes

Please note that these screws have a
reduced diameter shank and should not be
tightened to the recommended torque for
an equivalent machine screw of size d₁.

Order No.	d ₁	l ₁ ±0.25	d ₂ ±0.12	d ₃ min.	h ₁ max.	l ₂ ±0.25	A/F
T0158.030-010-A4	M 3	10	2.0	3.5	2.2	4.5	6
T0158.080-016-A4	M 8	16	6.0	8.5	5.3	10.0	13
T0158.080-035-A4	M 8	35	6.0	8.5	5.3	10.0	13